

# MAXIMUM INDICATING GAUGES

2½" Stainless Case or 4½" Cast Aluminum Case

## P2598LZSS-M

**CASE:** 300 series stainless steel.  
**RING:** 300 series stainless steel, bayonet type with gasket.  
**LENS:** Acrylic.  
**DIAL:** Aluminum, white finished with black markings.  
**POINTER:** Aluminum, black, non-adjustable.  
**MOVEMENT:** Stainless steel.  
**TUBE & SOCKET:** 316 Stainless steel.  
**CONNECTION:** 1/4" NPT bottom outlet.  
**ACCURACY:** ±1.6% Full Scale (exceeds ASME B40.100 Grade B).  
**PROCESS TEMPERATURE:** -40 to 250°F (-40 to 120°C).  
**AMBIENT TEMPERATURE:** -40 to 140°F (-40 to 60°C).

See Page 16 for further product specifications.



## P4509LX-M

**CASE:** Black cast-aluminum with a 3-hole surface-mount rear flange.  
**RING:** Stainless steel.  
**LENS:** Polycarbonate.  
**DIAL:** Aluminum, white finished with black markings.  
**POINTER:** Aluminum, black, micro-adjustable.  
**MOVEMENT:** Stainless steel rotary type.  
**TUBE & SOCKET:** Phosphor-bronze tube, brass socket.  
**CONNECTION:** 1/4" NPT brass, bottom outlet.  
**ACCURACY:** ±1/2% Full Scale (ASME B40.100 Grade 2A).  
**PROCESS TEMPERATURE:** -40 to 200°F (-40 to 93°C).  
**AMBIENT TEMPERATURE:** -40 to 140°F (-40 to 60°C).

See Page 3 for further product specifications.

