



General Specification

Case: High impact ABS black plastic
 Stem: Air Duct type
 Connection: 3 Hole mounting flange
 Sensor: Glass passivated thermistor
 Range: -58° to 302°F (-50° to 150°C)
 field-switchable between °F & °C
 Display: LCD, black character, 1/2" high with gray background
 Illuminance: Bi-directional solar collectors, 35 Lux
 Update Time: 6 times per minute
 Accuracy: Greater value of 1° or 1% of reading
 Resolution: 0.10° between -58° to 199.9°F (-50° to 93°C), 1° above 200°F
 Recalibration: Internal potentiometer
 Environmental Conditions:
 Ambient Temperature: -30° to 140°F (-35° to 60°C)
 Ambient Temperature Error: None
 Maximum Humidity: 100%

Customer: _____

Project: _____

Engineer: _____

Pro or PO#: _____

MILJOCO

CORPORATION 200 Elizabeth Street, Mt. Clemens, Michigan 48043 USA

SCALE: None	APPROVED BY:	DRAWN BY: HMT
DATE: 7/15/03		REVISED:

LCD Solar Digital Industrial Thermometer with Air Duct Stem

PART NUMBER: CDX9AD0685	DRAWING NUMBER: 127-214
DIMENSIONS: Inches [Metric] Inches: .xx ± .010 .xxx ± .005 [Metric]: .xx ± .25 .xxx ± .13	