

WATER & AIR TEST GAUGES

Utility Type - 2" Dial

Water Test Gauge

The Miljoco Water Test Gauge is ideal for testing the plumbing supply pressure of any point within a building. The gauge is furnished with a maximum indicating pointer, which will monitor any pressure surges over a period of time and can be easily reset after use.

General Specifications

- CASE:** Drawn steel, black finished.
LENS: Acrylic.
DIAL: Aluminum, white finished with black markings.
POINTER: Black.
MOVEMENT: Brass with precision-milled teeth.
TUBE & SOCKET: Brass
CONNECTION: 3/4" Female hose thread with swivel connection.
ACCURACY: ±3-2-3% (ASME B40.100 Grade B).
MAXIMUM INDICATING POINTER: Red, adjustable by user from exterior.
PROCESS TEMPERATURE: 32 to 140°F (0 to 60°C).
AMBIENT TEMPERATURE: -40 to 150°F (-40 to 65°C).



Models

Model	Range	Fig.	Div.
P2008U06HB	0-160 psi	40	2
P2008U08HB	0-300 psi	50	5

Air Test Gauge

- CASE:** Drawn steel, black finished.
LENS: Acrylic.
DIAL: Aluminum, white finished with black markings.
POINTER: Black.
MOVEMENT: Brass with precision-milled teeth.
TUBE & SOCKET: Brass
CONNECTION: Adapts to 3/4" NPT. Plated housing with bleed port.
ACCURACY: ±3-2-3% (ASME B40.100 Grade B).
PROCESS TEMPERATURE: 32 to 140°F (0 to 60°C).
AMBIENT TEMPERATURE: -40 to 150°F (-40 to 65°C).



Models

Model	Range	Fig.	Div.
P2008L02ATG	0-15 psi	1	0.1
P2008L03ATG	0-30 psi	5	0.5
P2008L04ATG	0-60 psi	10	1
P2008L05ATG	0-100 psi	20	2