

PRESSURE GAUGE ACCESSORIES

Snubbers & Syphons

Pressure Snubbers

Miljoco pressure gauge snubbers are designed to dampen pressure pulsations to prolong gauge life. They have a sintered stainless steel core with no moving parts, and are completely reliable to their maximum pressure rating. They can be piped together in pairs where severe pulsations exist.

Model	Body Material	Conn. Size	Maximum Pressure	Service
1200-25-B-1	Brass	1/4" NPT	1000 psi	Air & Other Gases
1200-25-B-2	Brass	1/4" NPT	1000 psi	Water & Light Oils
1200-25-B-3	Brass	1/4" NPT	1000 psi	Heavy Oils
1200-25-SS-1	303SS	1/4" NPT	2000 psi	Air & Other Gases
1200-25-SS-2	303SS	1/4" NPT	2000 psi	Water & Light Oils
1200-25-SS-3	303SS	1/4" NPT	2000 psi	Heavy Oils
1200-50-B-1	Brass	1/2" NPT	5000 psi	Air & Other Gases
1200-50-B-2	Brass	1/2" NPT	5000 psi	Water & Light Oils
1200-50-B-3	Brass	1/2" NPT	5000 psi	Heavy Oils
1200-50-SS-1	303SS	1/2" NPT	5000 psi	Air & Other Gases
1200-50-SS-2	303SS	1/2" NPT	5000 psi	Water & Light Oils
1200-50-SS-3	303SS	1/2" NPT	5000 psi	Heavy Oils



1200-25-B

High Pressure Pulsation Dampener

MODEL: 1250-25-B.
BODY MATERIAL: Brass.
CONNECTION SIZE: 1/4" NPT.
MAXIMUM PRESSURE: 5000 psi.
OPERATION: Spiral Helix.

Options

- Lead-Free: 1200-25-B-PBF

Coil Syphons

Miljoco coil syphons are required for use with gauges on steam lines, and are designed to form a barrier of water in the coil, preventing steam from attacking the bourdon tube solder joints.

Model	Material	Conn. Size	Maximum Pressure	Maximum Temp.
1300-25-CS	Welded Steel	1/4" NPT	600 psi	750°F
1300-25-B	Seamless Brass	1/4" NPT	250 psi	400°F
1300-25-304	Welded 304SS	1/4" NPT	1000 psi	650°F
1300-25-316	Welded 316SS	1/4" NPT	1000 psi	650°F
1300-50-CS	Welded Steel	1/2" NPT	600 psi	750°F
1300-50-304	Welded 304SS	1/2" NPT	1000 psi	650°F
1300-50-316	Welded 316SS	1/2" NPT	1000 psi	650°F



1300-25-CS